

# Mini thermometer

## Mini alarm thermometer

---

Settable min./max. alarm

---

Permanently attached probe

---

With a clip for standing up, wall installation or for attachment to clothing

---



Illustration 1:1

The affordable testo mini thermometer with alarm function is small and handy, but big on performance. The penetration probe has an 80 cm wire and is permanently fixed to the instrument. The probe and the wire can be easily and compactly stored in the instrument.


If individually settable limit values are violated, an audible signal is sounded. The minimum penetration depth of the probe tip should be 20 mm. The alarm thermometer is suitable for the recording of temperature in the air, in soft, powdery substances and in liquids. It is not suitable for use in ovens or fermentation cabinets.

## Technical data / Accessories

**Mini alarm thermometer**

Mini thermometer, battery included

Part no. 0900 0530



### Sensor type

Measuring range	-50 to +150 °C
Accuracy ±1 digit	±1 °C (-10 to +100 °C) ±2 °C (remaining range)
Resolution	0.1 °C (-19.9 to +150 °C) 1 °C (-50 to -20 °C)

### General technical data

Operating temperature	0 to +50 °C
Storage temperature	-20 to +70 °C
Battery type	2 AAA micro batteries
Battery life	100 h
Display	LCD, 1 line
Housing material	ABS
Warranty	2 years

0981 9414/msp/I/06.2017

Accessories	Part no.
<b>Accessories for measuring instrument</b>	
ISO calibration certificate/temperature; for air/immersion probes, calibration point -18°C	0520 0061
ISO calibration certificate/temperature; for air/immersion probes, calibration point 0°C	0520 0062

Subject to change without notice.

